

FTA-450L

AIR - BAND TRANSCEIVER

Huge Full-Dot Matrix Display and Advanced User Interface

Radio Features:

- 5 Watts TX Output Power (Air Band: AM 5W P.E.P. typ, 1.5W carrier)
- Huge 1.7" x 1.7" (43.2 x 43.2 mm) Full-Dot Matrix Display (160 x 160 dots)
- Loud Audio (800 mW)
- 8.33 kHz Narrow Band Compatible
- 200 Memory Channels with 15 alphanumeric characters
- Water Protection – IPX5 Rating
- Includes High-Capacity Rechargeable Li-Ion Battery Pack (7.4 V 1800 mAh)
- External-DC input for Operation and Charging
- Includes Alkaline Battery Tray (6 x AA)
- NOAA Weather Channel Receive*¹
- NOAA Weather Alert*¹
- Back-lit Keypad and Display with Dimmer
- BNC Antenna Connector
- PC Programmable (Included USB Cable)

Supplied Accessories:

- Antenna (SRA-13A)
- Belt Clip
- Li-Ion Battery Pack (SBR-12LI 7.4V, 1800 mAh)
- Charger Cradle (SBH-11)
- Cigarette Lighter DC/DC Converter (SDD-12)
- Headset Adapter Cable (SCU-15)
- Alkaline Battery Tray (SBT-12 6 x AA)
- USB Cable (T9101606)
- Operating Manual
- Warranty Card

Specifications:

Frequency Ranges:	RX	118.000 to 136.975 MHz 161.650 to 163.275 MHz (Weather Channels)
	TX	118.000 to 136.975 MHz
Channel Spacing:		25 kHz/8.33 kHz
Emission Type:		TX: AM RX: AM & FM
RF Power Output:		5.0 W (PEP), 1.5 W (Carrier Power)
Water Protection Rating:		IPX5
Case Size(W x H x D):		2.4" x 5.2" x 1.3" (62 x 133 x 34 mm) w/o Knob & Antenna
Weight:		14.5 oz (410 g) w/ SBR-12LI, Antenna and Belt Clip
Qty in Master Carton:		FTA-450L : 10
Warranty:		3 Years



FTA-450L

*1 Only available in NOAA weather service areas